ABSTRACT

Microstrip antenna as one of the main components of wireless communication

is one solution in compliance with the antenna design has a variety of advantages. One

of the advantages of Microstrip antenna is a patch that can be modified to suit the

needs of the user.

Double E shaped is one of the method to modify the microstrip antenna with

some element variation so it can work in several different frequency in one device

antenna. The design is done with use of an extra slot on the design as well as with

supply the microstrip line feeds. This final project have done a design, simulation, and

realization of a double E shaped antenna with modified patch microstrip antenna

working at a frequency of 2.4 GHz, 3.4 GHz, and 5.8 GHz. The design is done by using

an extra slot on patch antenna using microstrip line supply feed. Using the CST Studio

Suite to analyze the result, the results needs to meet the specification of Return Loss <-

10 dB, VSWR < 2, bandwidth 100 MHz for 2.4 and 3.4 GHz, 125 MHz for 5.8 GHz,

gain > 3 dBi, unidirectional radiation pattern and linear type of polarization. The

materials used for the substrate is FR-4 epoxy with the relative permittivity 4.4 and

thickness of 1.6 mm.

As the measurements results showed this antenna generates a Return Loss in

each of the working frequency of -11.72, -11,792, -21.33 with a value of VSWR 1,774,

1,683, 1,157. Impedance obtained 43.28 ohm, 43,082 ohm 34,112 ohm. Each gain of

3.47 dB, 3.51 dB, and 3.53 dB with 64.2 MHz, 67.52 MHz, and 100.08 MHz of

bandwidth, unidirectional radiation pattern and ellips type of polarization.

Keywords: Double E shaped, microstrip, multiband

v