

DAFTAR GAMBAR

Gambar 2.1. Arsitektur LTE	5
Gambar 2.2. Perangkat <i>Multi Network Combiner System</i>	13
Gambar 3.1. <i>Flowchart</i> Penanganan Interferensi Secara Umum	15
Gambar 3.2. Langkah (1) <i>user login</i> aplikasi iManager U2000	16
Gambar 3.3. Langkah (2) <i>Channel Quality Measurement</i>	17
Gambar 3.4. Langkah (3) counter untuk memilih data	17
Gambar 3.5. Langkah (4) pengaturan waktu	18
Gambar 3.6. Langkah (5) <i>download</i> data.....	18
Gambar 3.7. Langkah (6) hasil <i>Download Data</i>	19
Gambar 3.8. <i>Flowchart</i> Penanganan <i>Indoor Interference</i>	20
Gambar 3.9. Halaman <i>Login Remedy</i>	23
Gambar 3.10. Tiket Keluhan Pelanggan	23
Gambar 3.11. Detail Tiket Keluhan Pelanggan	24
Gambar 3.12. Grafik <i>L.UL Interference</i> (before)	25
Gambar 3.13. Grafik CSSR (before).....	26
Gambar 3.14. Grafik Service Drop Rate (before).....	26
Gambar 3.15. Grafik <i>Cell Downlink Average Throughput</i> (before)..	27
Gambar 3.16. Grafik <i>Cell Uplink Average Throughput</i> (before)	27
Gambar 3.17. Grafik <i>User Downlink Average Throughput</i> (before).28	
Gambar 3.18. Grafik <i>User Uplink Average Throughput</i> (before)	28
Gambar 3.19. Grafik <i>Downlink Traffic Volume</i> (before).....	29
Gambar 3.20. Grafik <i>Uplink Traffic Volume</i> (before)	29
Gambar 3.21. Tampilan <i>real-time</i> rata- rata RTWP (before).....	30
Gambar 3.22. Lokasi Pengecekan di site	31
Gambar 3.23. Penggantian perangkat <i>Multi Network Combiner System</i>	32
Gambar 4.1. Lokasi Interferensi dan <i>Site Information</i>	33
Gambar 4.2. Grafik <i>L.UL Interference</i> (after).....	34
Gambar 4.3. Grafik CSSR (after)	34
Gambar 4.4. Grafik Service Drop Rate (after)	35

Gambar 4.5. Grafik <i>Cell Downlink Average Throughput</i> (after)	35
Gambar 4.6. Grafik <i>Cell Uplink Average Throughput</i> (after)	36
Gambar 4.7. Grafik <i>User Downlink Average Throughput</i> (after)	36
Gambar 4.8. Grafik <i>User Uplink Average Throughput</i> (after)	37
Gambar 4.9. Grafik <i>Downlink Traffic Volume</i> (after)	37
Gambar 4.10. Grafik <i>Uplink Traffic Volume</i> (after)	38
Gambar 4.11. Tampilan <i>real-time</i> rata- rata RTWP (after)	38