

DAFTAR PUSTAKA

- [1] Xiao Li, H. Z. (2015). Two-dimensional MoS₂: Properties, preparation, and applications. *Materiomics*, 33-44.
- [2] Hai Li, J. W. (2014). Preparation and Applications of Mechanically Exfoliated Single Layer and Multilayer MoS₂ and WSe₂ Nanosheets. *ACS Publications*, 1067-1075.
- [3] Xinsheng Wang, H. F. (2013). Controlled Synthesis of Highly Crystalline MoS₂ Flakes by Chemical Vapor Deposition. *ACS Publications*.
- [4] Ridwan F.Hossain, I. G. (2017). Biocompatible, large-format, inkjed printed heterostructure MoS₂-graphene photodetectors on conformable substrates. *Nature Partner Journals*.
- [5] Jongwon Yoon *et al* (2013). Highly Flexible and Transparent Multilayer MoS₂ Transistors with Graphene electrodes. *Small*, 1-6.
- [6] Lee, K. (2011). Electrical Characteristics of Molybdenum Disulfide Flakes Produced by Liquid Exfoliation. *advanced material*, 4178-4182.
- [7] Yang, H. (2017). Highly Scalable Synthesis of MoS₂ Thin Films with Precise Thickness Control via Polymer-Assisted Deposition. *Chemistry of materials*, 5772-5776.
- [8] *Cost Effective Equipment*. "Spin Coat Theory",
<http://www.costeffectiveequipment.com/spin-coating-theory>,
(diakses tanggal 3 Desember 2018)
- [9] Bang, G. S. (2014). Effective Liquid-Phase Exfoliation and Sodium Ion Battery Application of MoS₂ Nanosheets. *ACS Publications*, 7084-7089.
- [10] Kai Liu.(2015).Mechanical properties of two-dimensional materials and heterostructures, 324
- [11] Zuoli He, W. Q. (2016). Molybdenum Disulfide nanomaterials : Structure, properties, synthesis and recent progress on hydrogen evolution reaction. *Elsevier*, 2352-9407.
- [12] Sean P Ogilvie *et al*.(2017).Considerations fo spectroscopy of liquid exfoliated 2D Materials : emerging photoluminescence of N-Methyl-2-Pyrrolidone, 1-7.

- [13] Artur Ciesielski.(2016).Graphene via sonication assisted liquid-phase exfoliation, 381.
- [14] Raed K. Al-Tamimi.(2011). Moayad N. Khalaf, May Sabri, Luma Sabri, “Post Consumer polyethylene terephthalate depolymerization by waste of battery acid hydrolysis”.
- [15] M.G.Faraj.(2011).PET as a plastic substrate for the flexible optoelectronic applications. 879-882.
- [16] Phoenix Technology International LLC., “*Polyethylene Terephthalate Key Properties*”.<http://www.phoenixtechnologies.net/media> (diakses tanggal 28 Oktober 2018).
- [17] Sarah Annisa.(2018). “*Electrical Properties Of MoS₂ On Flexible Substrate PET*”.
- [18] Do-Hyoung Kim, Han-Ki Yoon, Do-Hoon Shin, Ri-Ichi Murakami “*Mechanical properties of ITO/PET Thin Film Deposited by DC MG Method*”. 2005.
- [19] Wahid Shams. Electrical, Optical and Structural Properties of Improved Transparent Conductive Oxide TCO Films. 2014.
- [20] L. Filipovic: Topography Simulation of Novel Processing Techniques, “*Silicon Dioxide Properties*”, <http://www.iue.tuwien.ac.at/phd/filipovic/node26.html> , (diakses tanggal 19 Oktober 2018)
- [21] Yongjie Zhan.(2012). Large-Area Vapor-Phase Growth and Characterization of MoS₂ Atomic Layers on a SiO₂ Substrate. *Small*. No.7, 966-971.
- [22] Specialty Coating Systems. (n.d.). Indianapolis, IN 46278-2707, 7645 Woodland Drive.
- [23] Asrofi Khoirul Huda, Achmad Maulana, Ichsanul Huda, Diky Anggoro.(2015). Penerapan Spin Coating untuk Pembuatan Lapisan Tipis dengan MMA.
- [24] Marco Bernardi, Maurizia Palummo and Jeffrey. (2015). Extraordinary Sunlight Absorption and 1 nm-Thick Photovoltaics using Two-Dimensional Monolayer Materials.