

## DAFTAR TABEL

<b>Tabel 2.1</b> Spesifikasi <i>Long Term Evolution</i> .....	5
<b>Tabel 2.2</b> <i>Service and Traffic Model Parameter</i> .....	15
<b>Tabel 2.3</b> Nilai Umum untuk <i>Peak to Average Ratio Indoor</i> .....	16
<b>Tabel 2.4</b> <i>Average SINR Distribution</i> .....	18
<b>Tabel 2.5</b> <i>Bandwidth &amp; Resource Block (RB)</i> .....	19
<b>Tabel 2.6</b> <i>Peak Data Rate</i> .....	20
<b>Tabel 3.1</b> Spesifikasi Gedung Pasar Baru Bandung .....	24
<b>Tabel 3.2</b> Spesifikasi Jaringan 4G <i>indoor</i> operator XL .....	24
<b>Tabel 3.3</b> Skala RSRP Standar Operator .....	26
<b>Tabel 3.4</b> Skala SINR Standar Operator .....	28
<b>Tabel 3.5</b> Skala <i>Throughput</i> Standar Operator.....	29
<b>Tabel 3.6</b> Total <i>user</i> maksimum Lt.6 .....	31
<b>Tabel 3.7</b> <i>Service Model Parameter</i> .....	31
<b>Tabel 3.8</b> <i>Single User Throughput</i> .....	32
<b>Tabel 3.9</b> <i>Total Network Throughput (IP &amp; MAC)</i> .....	33
<b>Tabel 3.10</b> <i>Average SINR 850 MHz Distribution Single Site Throughput</i> .....	33
<b>Tabel 3.11</b> <i>Site Calculation</i> .....	34
<b>Tabel 4.1</b> Jumlah <i>lampsite</i> .....	35
<b>Tabel 4.2</b> Parameter Performasi di Lt.6 Gedung Pasar Baru Bandung .....	40
<b>Tabel 4.3</b> Rangkaian <i>Before</i> dan <i>After</i> simulasi .....	47