

DAFTAR PUSTAKA

- Athreya, S., & Venkatesh, Y. D. (2012). *Application Of Taguchi Method For Optimization Of Process Parameters In Improving The Surface Roughness Of Lathe Facing Operation*. 1(3), 13–19.
- Baykasoğlu, A., Baykasoğlu, C., & Cetin, E. (2020). Multi-objective crashworthiness optimization of lattice structure filled thin-walled tubes. *Thin-Walled Structures*, 149(October 2019).
<https://doi.org/10.1016/j.tws.2020.106630>
- Bussadori, B. P., Schuffenhauer, K., & Scattina, A. (2014). Modelling of CFRP crushing structures in explicit crash analysis. *Composites Part B: Engineering*, 60, 725–735.
<https://doi.org/10.1016/j.compositesb.2014.01.020>
- Chen, B. C., Zou, M., Liu, G. M., Song, J. F., & Wang, H. X. (2018). Experimental study on energy absorption of bionic tubes inspired by bamboo structures under axial crushing. *International Journal of Impact Engineering*, 115(January), 48–57. <https://doi.org/10.1016/j.ijimpeng.2018.01.005>
- David, S., Damayanti, D. D., & Eka, D. S. (2016). Optimasi Sensor Kamera pada Proses Identifikasi Warna dengan Pengolahan Citra Menggunakan Design Of Experiment. *E-Proceeding Of Engineering*, Vol.3(No.2), 3050.
- Do, K., Nam, D., & Taik, H. (2004). *Optimization of experimental conditions based on the Taguchi robust design for the formation of nano-sized silver particles by chemical reduction method*. 104, 55–61.
<https://doi.org/10.1016/j.cej.2004.08.003>
- Estrada, Q., Szwedowicz, D., Rodriguez-Mendez, A., Elías-Espinosa, M., Silva-Aceves, J., Bedolla-Hernández, J., & Gómez-Vargas, O. A. (2019). Effect of radial clearance and holes as crush initiators on the crashworthiness performance of bi-tubular profiles. *Thin-Walled Structures*, 140(December 2018), 43–59. <https://doi.org/10.1016/j.tws.2019.02.039>
- Fazita, M. R. N., Khalil, H. P. S. A., Izzati, A. N. A., & Rizal, S. (2019). 3 - Effects of strain rate on failure mechanisms and energy absorption in polymer composites. In *Failure Analysis in Biocomposites, Fibre-Reinforced*

Composites and Hybrid Composites. <https://doi.org/10.1016/B978-0-08-102293-1.00003-6>

- Fratila, D., & Caizar, C. (2011). Application of Taguchi method to selection of optimal lubrication and cutting conditions in face milling of AlMg3. *Journal of Cleaner Production*, 19(6–7), 640–645. <https://doi.org/10.1016/j.jclepro.2010.12.007>
- Freddi, A., & Salmon, M. (2019). Design of experiment. In *Springer Tracts in Mechanical Engineering*. https://doi.org/10.1007/978-3-319-95342-7_6
- Fu, J., Liu, Q., Liufu, K., Deng, Y., Fang, J., & Li, Q. (2019). Design of bionic-bamboo thin-walled structures for energy absorption. *Thin-Walled Structures*, 135(October 2018), 400–413. <https://doi.org/10.1016/j.tws.2018.10.003>
- Gamage, A., & Hyde, R. (2012). A model based on Biomimicry to enhance ecologically sustainable design. *Architectural Science Review*, 55(3), 224–235. <https://doi.org/10.1080/00038628.2012.709406>
- Hu, D., Wang, Y., Song, B., Dang, L., & Zhang, Z. (2019). Energy-absorption characteristics of a bionic honeycomb tubular nested structure inspired by bamboo under axial crushing. *Composites Part B: Engineering*, 162(October 2018), 21–32. <https://doi.org/10.1016/j.compositesb.2018.10.095>
- Jones, N. (2003). Several phenomena in structural impact and structural crashworthiness. *European Journal of Mechanics, A/Solids*, 22(5), 693–707. [https://doi.org/10.1016/S0997-7538\(03\)00077-9](https://doi.org/10.1016/S0997-7538(03)00077-9)
- Liu, Q., Wang, J., Huang, X., Wu, T., Zong, Z., & Li, Q. (2018). In-plane and out-of-plane bending responses of aluminum mortise-tenon joints in lightweight electric vehicle inspired by timber structures. *Thin-Walled Structures*, 127(January), 169–179. <https://doi.org/10.1016/j.tws.2018.01.033>
- Liu, Q., Xu, X., Ma, J., Hu, Z., & Hui, D. (2017). Energy absorption of bio-inspired multi-cell CFRP and aluminum square tubes. *Composites Part B*. <https://doi.org/10.1016/j.compositesb.2017.03.034>
- Lu, G., & Yu, T. (2011). Energy absorption of structures and materials. *Energy Absorption of Structures and Materials*, 1–24. <https://doi.org/10.1533/9781855738584.1>

- M. Versos, C. A., & A., D. (2011). Biologically Inspired Design: Methods and Validation. *Industrial Design - New Frontiers*, (May).
<https://doi.org/10.5772/20326>
- Mahadevan, K., Liang, P., & Fekete, J. (2000). Effect of strain rate in full vehicle frontal crash analysis. *SAE Technical Papers*, (724).
<https://doi.org/10.4271/2000-01-0625>
- Mahmoodi, A., Shojaeefard, M. H., & Saeidi Googarchin, H. (2016). Theoretical development and numerical investigation on energy absorption behavior of tapered multi-cell tubes. *Thin-Walled Structures*, 102, 98–110.
<https://doi.org/10.1016/j.tws.2016.01.019>
- Marsolek, J., & Reimerdes, H. G. (2004). Energy absorption of metallic cylindrical shells with induced non-axisymmetric folding patterns. *International Journal of Impact Engineering*, 30(8–9), 1209–1223.
<https://doi.org/10.1016/j.ijimpeng.2004.06.006>
- Mohamed, A. S., Laban, O., Tarlochan, F., Al Khatib, S. E., Matar, M. S., & Mahdi, E. (2019). Experimental analysis of additively manufactured thin-walled heat-treated circular tubes with slits using AlSi10Mg alloy by quasi-static axial crushing test. *Thin-Walled Structures*, 138(October 2018), 404–414. <https://doi.org/10.1016/j.tws.2019.02.022>
- Nia, A. A., & Hamedani, J. H. (2010). Comparative analysis of energy absorption and deformations of thin walled tubes with various section geometries. *Thin-Walled Structures*, 48(12), 946–954.
<https://doi.org/10.1016/j.tws.2010.07.003>
- Roy, R. (2001). Design of Experiment Using The Taguchi Approach: 16 step to product and process improvement. *Technometrics*.
<https://doi.org/10.1198/004017002320256440>
- Sidi, P., & Wahyudi, M. T. (2013). Aplikasi Metoda Taguchi Untuk Mengetahui Optimasi Kebulatan Pada Proses Bubut Cnc. *Jurnal Rekayasa Mesin*, 4(2), 101–108.
- Verma, D., & Senal, I. (2019). Natural fiber-reinforced polymer composites. In *Biomass, Biopolymer-Based Materials, and Bioenergy: Construction, Biomedical, and other Industrial Applications*. <https://doi.org/10.1016/B978->

0-08-102426-3.00006-0

- Volstad, N. L., & Boks, C. (2012). *On the use of Biomimicry as a Useful Tool for the Industrial Designer*. 199(7491), 189–199.
<https://doi.org/10.1002/sd.1535>
- Yang, F., Fan, H., & Meguid, S. A. (2019). Effect of foam-filling on collapse mode transition of thin-walled circular columns under axial compression: Analytical, numerical and experimental studies. *International Journal of Mechanical Sciences*, 150, 665–676.
<https://doi.org/10.1016/j.ijmecsci.2018.10.047>
- Yao, R. yang, Yin, G. sheng, Hao, W. qian, Zhao, Z. yu, Li, X., & Qin, X. li. (2019). Axial buckling modes and crashworthiness of circular tube with external linear gradient grooves. *Thin-Walled Structures*, 134(September 2018), 395–406. <https://doi.org/10.1016/j.tws.2018.10.022>
- Zhang, J. Z., Chen, J. C., & Kirby, E. D. (2007). Surface roughness optimization in an end-milling operation using the Taguchi design method. *Journal of Materials Processing Technology*, 184(1–3), 233–239.
<https://doi.org/10.1016/j.jmatprotec.2006.11.029>
- Zhang, X., & Zhang, H. (2013). Thin-Walled Structures Energy absorption of multi-cell stub columns under axial compression. *Thin Walled Structures*, 68, 156–163. <https://doi.org/10.1016/j.tws.2013.03.014>
- Zhang, Y., Sun, G., Li, G., Luo, Z., & Li, Q. (2012). Optimization of foam-filled bitubal structures for crashworthiness criteria. *Materials and Design*, 38, 99–109. <https://doi.org/10.1016/j.matdes.2012.01.028>
- Zou, M., Song, J., Xu, S., Liu, S., & Chang, Z. (2018). Bionic design of the bumper beam inspired by the bending and energy absorption characteristics of bamboo. *Applied Bionics and Biomechanics*, 2018.
<https://doi.org/10.1155/2018/8062321>
- Zou, M., Xu, S., Wei, C., Wang, H., & Liu, Z. (2016). A bionic method for the crashworthiness design of thin-walled structures inspired by bamboo. *Thin-Walled Structures*, 101, 222–230. <https://doi.org/10.1016/j.tws.2015.12.023>