

DAFTAR PUSTAKA

- [1] Z. Ghassemlooy, W. Popoola, and S. Rajbhandari, *Optical wireless communications: system and channel modelling with Matlab®*. CRC press, 2019.
- [2] R. C. Kizilirmak, C. R. Rowell, and M. Uysal, “Non-orthogonal multiple access (noma) for indoor visible light communications,” in *2015 4th international workshop on optical wireless communications (IWOW)*. IEEE, 2015, pp. 98–101.
- [3] K. Kadam and M. R. Dhage, “Visible light communication for iot,” in *2016 2nd International Conference on Applied and Theoretical Computing and Communication Technology (iCATccT)*. IEEE, 2016, pp. 275–278.
- [4] S. S. Bawazir, P. C. Sofotasios, S. Muhamadat, Y. Al-Hammadi, and G. K. Karagiannidis, “Multiple access for visible light communications: Research challenges and future trends,” *IEEE Access*, vol. 6, pp. 26 167–26 174, 2018.
- [5] P. H. Pathak, X. Feng, P. Hu, and P. Mohapatra, “Visible light communication, networking, and sensing: A survey, potential and challenges,” *IEEE communications surveys & tutorials*, vol. 17, no. 4, pp. 2047–2077, 2015.
- [6] T. Manglayev, R. C. Kizilirmak, Y. H. Kho, N. Bazhayev, and I. Lebedev, “Noma with imperfect sic implementation,” in *IEEE EUROCON 2017-17th International Conference on Smart Technologies*. IEEE, 2017, pp. 22–25.
- [7] C. Chen, W.-D. Zhong, H. Yang, P. Du, and Y. Yang, “Flexible-rate sic-free noma for downlink vlc based on constellation partitioning coding,” *IEEE Wireless Communications Letters*, vol. 8, no. 2, pp. 568–571, 2018.

- [8] X. Guan, Q. Yang, and C.-K. Chan, “Joint detection of visible light communication signals under non-orthogonal multiple access,” *IEEE Photonics Technology Letters*, vol. 29, no. 4, pp. 377–380, 2017.
- [9] T. Yazaki and Y. Sanada, “Effect of joint detection and decoding in non-orthogonal multiple access,” in *2014 International Symposium on Intelligent Signal Processing and Communication Systems (ISPACS)*. IEEE, 2014, pp. 245–250.
- [10] R. H. A. Prastica, “Analisis pengaruh penambahan reflector terhadap tegangan keluaran modul solar cell,” Ph.D. dissertation, Universitas Muhammadiyah Surakarta, 2016.
- [11] S. D. Dissanayake and J. Armstrong, “Comparison of aco-ofdm, dco-ofdm and ado-ofdm in im/dd systems,” *Journal of lightwave technology*, vol. 31, no. 7, pp. 1063–1072, 2013.
- [12] H. Marshoud, V. M. Kapinas, G. K. Karagiannidis, and S. Muhaidat, “Non-orthogonal multiple access for visible light communications,” *IEEE photonics technology letters*, vol. 28, no. 1, pp. 51–54, 2015.
- [13] S. I. Bross, A. Lapidoth, and M. A. Wigger, “The gaussian mac with conferencing encoders,” in *2008 IEEE International Symposium on Information Theory*. IEEE, 2008, pp. 2702–2706.
- [14] S. Chen, K. Peng, and H. Jin, “A suboptimal scheme for uplink noma in 5g systems,” in *2015 International Wireless Communications and Mobile Computing Conference (IWCMC)*. IEEE, 2015, pp. 1429–1434.
- [15] J. G. Andrews and T. H. Meng, “Optimum power control for successive interference cancellation with imperfect channel estimation,” *IEEE Transactions on Wireless Communications*, vol. 2, no. 2, pp. 375–383, 2003.

- [16] H. Marshoud, S. Muhaidat, P. C. Sofotasios, S. Hussain, M. A. Imran, and B. S. Sharif, “Optical non-orthogonal multiple access for visible light communication,” *IEEE Wireless Communications*, vol. 25, no. 2, pp. 82–88, 2018.