

LIST OF FIGURES

| | | |
|------|---|----|
| 2.1 | SDN architecture. | 5 |
| 2.2 | Example Topology | 7 |
| 2.3 | OpenFlow architech | 8 |
| 3.1 | sflow-rt Captured Normal Traffic | 13 |
| 3.2 | sflow-rt Captured DDoS Traffic | 13 |
| 3.3 | Interface of Wireshark | 14 |
| 3.4 | Wireshark-Capture File Properties | 15 |
| 3.5 | Iperf Sending Traffic | 15 |
| 3.6 | Iperf Sending Traffic 2 | 16 |
| 3.7 | Simulation Sequence. | 17 |
| 3.8 | Network Topology. | 18 |
| 3.9 | Flowchart Controller. | 20 |
| 3.10 | Collecting Normal Traffic. | 22 |
| 3.11 | Collecting DDoS Traffic. | 22 |
| 3.12 | Result on csv. | 23 |
| 3.13 | SVM Detect Normal Traffic. | 23 |
| 3.14 | SVM Detect DDoS Traffic. | 24 |
| 3.15 | Blocking Port. | 24 |
| 3.16 | SVM Decision Boundary 1. | 24 |
| 3.17 | SVM Decision Boundary 2. | 25 |
| 3.18 | Down Time in Iperf | 26 |
| 3.19 | Down Time in Iperf | 27 |
| 4.1 | Throughput of Normal traffic | 29 |
| 4.2 | DDoS Throughput Without Attack Mitigation | 30 |
| 4.3 | Throughput of DDoS Attack with SVM mitigation | 31 |
| 4.4 | Throughput Comparison Between 5 Attackers | 32 |
| 4.5 | Down Time of Simulation | 33 |
| 4.6 | Recovery Time of Simulation | 34 |
| 4.7 | Accuracy of the simulation | 35 |