

LIST OF IMAGES

Figure 1.1. Block diagram of the system in BSS	15
Figure 2.1. Li-Ion Battery Charging Curve by Experiment	21
Figure 2.2. Li-Ion Battery Discharging Curve	21
Figure 2.3. Structure of LSTM cell	23
Figure 3.1. 8 Pin M23 socket for batteries from Gesits brands	25
Figure 3.2. Variable Charger	26
Figure 3.3. Lifepo4 Battery	26
Figure 3.4. Battery for Gesits brand electric motorcycle	27
Figure 3.5. BSS system structure	28
Figure 3.6. Schematic of Rolling Horizon Optimization	29
Figure 3.7. Flowchart of the system at the station	30
Figure 4.1. Comparison chart of Training Loss and Validation Loss	38
Figure 4.2. Hyperparameter of Polynomial Regression	38
Figure 4.3. Hyperparameter of LSTM	39
Figure 4.4. Prediction results using polynomial regression	40
Figure 4.5. Prediction results using LSTM before denormalization	41
Figure 4.6. The Battery Demand of on The End of Workdays	42
Figure 4.7. The Battery Swapped by RHO-LSTM Method	42
Figure 4.8. The BSS Power Curves vs Real Time Price with RHO-LSTM	43
Figure 4.9. The Battery Swapped by RHO-Polynomial Regression Method	43
Figure 4.10. The BSS Power Curves vs Real Time Price with RHO-Polynomial Regression	44
Figure 4.11. The BSS Power Curves vs Grid Price with RHO-LSTM and RHO- Polynomial Regression	44
Figure 4.12. The BSS Profit	46
Figure 4.13. Charging power of Gesits battery	47