

#### IV. CONCLUSION

In this work, we proposed a hybrid itinerary planning model for WSN in BSHM. Our model integrates the benefits of utilizing a genetic algorithm for static route planning and making dynamic adjustments to ensure network functionality, even in the case of node failures during data transmission. This hybrid strategy guarantees the collection of data that is strong and dependable by overcoming the shortcomings of classic static approaches that are susceptible to interruptions when nodes become inaccessible. Furthermore, our model integrates a peak detection technique to selectively process incoming vibration data produced by the bridge. Ensuring the cleanliness and accuracy of the data processed by the FFT is a vital step that leads to more trustworthy analysis and monitoring findings. By using peak detection, the sensor network can effectively filter out noise and irrelevant data, thereby improving the quality and reliability of the provided structural health information. The experimental results showed that the hybrid itinerary planning model, although it takes slightly longer to process than the static method, greatly enhances the network's capacity to recover quickly and maintain consistent performance. The hybrid architecture effectively sustained data transmission and processing despite node failures, demonstrating its resilience in real-world circumstances where node failures resulting from physical damage or energy depletion are frequent. The decision to balance processing time and network robustness is supported by the improved performance and dependability of the WSN in BSHM applications.

#### REFERENCES

- [1] X. Insausti, M. Zárraga-Rodríguez, C. Nolasco-Ferencikova, and J. Gutiérrez-Gutiérrez, "In-Network Algorithm for Passive Sensors in Structural Health Monitoring," *IEEE Signal Process. Lett.*, vol. 30, pp. 952–956, 2023, doi: 10.1109/LSP.2023.3298279.
- [2] F. Di Nuzzo, D. Brunelli, T. Polonelli, and L. Benini, "Structural Health Monitoring System With Narrowband IoT and MEMS Sensors," *IEEE Sens. J.*, vol. 21, no. 14, pp. 16371–16380, Jul. 2021, doi: 10.1109/JSEN.2021.3075093.
- [3] Y. Pan, L. Zhang, X. Wu, K. Zhang, and M. J. Skibniewski, "Structural health monitoring and assessment using wavelet packet energy spectrum," *Saf. Sci.*, vol. 120, pp. 652–665, Dec. 2019, doi: 10.1016/j.ssci.2019.08.015.
- [4] Z. Deng, M. Huang, N. Wan, and J. Zhang, "The Current Development of Structural Health Monitoring for Bridges: A Review," *Buildings*, vol. 13, no. 6, p. 1360, May 2023, doi: 10.3390/buildings13061360.
- [5] X. Wang, W. Wu, Y. Du, J. Cao, Q. Chen, and Y. Xia, "Wireless IoT Monitoring System in Hong Kong–Zhuhai–Macao Bridge and Edge Computing for Anomaly Detection," *IEEE Internet Things J.*, vol. 11, no. 3, pp. 4763–4774, Feb. 2024, doi: 10.1109/JIOT.2023.3300073.
- [6] D. S. Kumar, S. Saravana Sundaram, S. Prakash, and S. Selvaperumal, "Effective Aggregate Data Collection and Enhanced Network Lifetime Using Energy Efficient Aggregation Data Convening Routing in Wireless Sensor Network," *Wirel. Pers. Commun.*, vol. 131, no. 1, pp. 89–103, Jul. 2023, doi: 10.1007/s11277-023-10419-y.
- [7] S. Chaudhary, U. Kumar, and S. Gambhir, "Energy-Efficient and Secured Mobile Agent Itinerary Approach in Wireless Sensor Network," in *Innovations in Electrical and Electronic Engineering*, vol. 661, M. N. Favorskaya, S. Mekhilef, R. K. Pandey, and N. Singh, Eds., in Lecture Notes in Electrical Engineering, vol. 661, Singapore: Springer Singapore, 2021, pp. 693–711. doi: 10.1007/978-981-15-4692-1\_53.
- [8] S. A. Putra, B. R. Trilaksono, M. Riyansyah, D. S. Laila, A. Harsoyo, and A. I. Kistijantoro, "Intelligent Sensing in Multiagent-Based Wireless Sensor Network for Bridge Condition Monitoring System," *IEEE Internet Things J.*, vol. 6, no. 3, pp. 5397–5410, Jun. 2019, doi: 10.1109/JIOT.2019.2901796.
- [9] W. Wang, H. Huang, Q. Li, F. He, and C. Sha, "Generalized Intrusion Detection Mechanism for Empowered Intruders in Wireless Sensor Networks," *IEEE Access*, vol. 8, pp. 25170–25183, 2020, doi: 10.1109/ACCESS.2020.2970973.
- [10] M. Sidorov, P. V. Nhut, Y. Matsumoto, and R. Ohmura, "LoRa-Based Precision Wireless Structural Health Monitoring System for Bolted Joints in a Smart City Environment," *IEEE Access*, vol. 7, pp. 179235–179251, 2019, doi: 10.1109/ACCESS.2019.2958835.
- [11] A. Bohloulzadeh and M. Rajaei, "A Survey on Congestion Control Protocols in Wireless Sensor Networks," *Int. J. Wirel. Inf. Netw.*, vol. 27, no. 3, pp. 365–384, Sep. 2020, doi: 10.1007/s10776-020-00479-3.
- [12] K. Guravaiah, A. Kavitha, and R. Leela Velusamy, "Data Collection Protocols in Wireless Sensor Networks," in *Wireless Sensor Networks - Design, Deployment and Applications*, S. S. Yellampalli, Ed., IntechOpen, 2021. doi: 10.5772/intechopen.93659.
- [13] M. N. Khan *et al.*, "Improving Energy Efficiency With Content-Based Adaptive and Dynamic Scheduling in Wireless Sensor Networks," *IEEE Access*, vol. 8, pp. 176495–176520, 2020, doi: 10.1109/ACCESS.2020.3026939.
- [14] A. R. Al-Ali *et al.*, "An IoT-Based Road Bridge Health Monitoring and Warning System," *Sensors*, vol. 24, no. 2, p. 469, Jan. 2024, doi: 10.3390/s24020469.
- [15] A. Moallemi, A. Burrello, D. Brunelli, and L. Benini, "Exploring Scalable, Distributed Real-Time Anomaly Detection for Bridge Health Monitoring," *IEEE Internet Things J.*, vol. 9, no. 18, pp. 17660–17674, Sep. 2022, doi: 10.1109/JIOT.2022.3157532.
- [16] E. M. Tronci, S. Nagabuko, H. Hieda, and M. Q. Feng, "Long-Range Low-Power Multi-Hop Wireless Sensor Network for Monitoring the Vibration Response of Long-Span Bridges," *Sensors*, vol. 22, no. 10, p. 3916, May 2022, doi: 10.3390/s22103916.
- [17] M. Z. Sarwar, M. R. Saleem, J.-W. Park, D.-S. Moon, and D. J. Kim, "Multimetric Event-Driven System for Long-Term Wireless Sensor Operation for SHM Applications," *IEEE Sens. J.*, vol. 20, no. 10, pp. 5350–5359, May 2020, doi: 10.1109/JSEN.2020.2970710.
- [18] Y. Liu, T. Voigt, N. Wirstrom, and J. Hoglund, "EcoVibe: On-Demand Sensing for Railway Bridge Structural Health Monitoring," *IEEE Internet Things J.*, vol. 6, no. 1, pp. 1068–1078, Feb. 2019, doi: 10.1109/JIOT.2018.2867086.
- [19] F. F. Jurado-Lasso, K. Clarke, A. N. Cadavid, and A. Nirmalathas, "Energy-Aware Routing for Software-Defined Multihop Wireless Sensor Networks," *IEEE Sens. J.*, vol. 21, no. 8, pp. 10174–10182, Apr. 2021, doi: 10.1109/JSEN.2021.3059789.
- [20] I. Lahmar, A. Zaier, M. Yahia, J. Lloret, and R. Bouallegue, "Optimal data transmission for decentralized IoT and WSN based on Type-2 Fuzzy Harris Hawks Optimization," *Internet Things*, vol. 25, p. 101028, Apr. 2024, doi: 10.1016/j.iot.2023.101028.
- [21] E. Hidalgo Fort *et al.*, "Wireless and Low-Power System for Synchronous and Real-Time Structural-Damage Assessment," *IEEE Sens. J.*, vol. 23, no. 12, pp. 13648–13658, Jun. 2023, doi: 10.1109/JSEN.2023.3270961.
- [22] K. S. Rajeshwari and K. A. S. Devi, "Fault Tolerance and Energy Efficient Multi-Hop Clustering with Dual Base Stations in Large Scale Wireless Sensor Network," *SN Comput. Sci.*, vol. 4, no. 3, p. 309, Apr. 2023, doi: 10.1007/s42979-023-01745-w.
- [23] N. Hrovatin, A. Tošić, and J. Vičić, "In-Network Convolution in Grid Shaped Sensor Networks," *J. Web Eng.*, Nov. 2021, doi: 10.13052/jwe1540-9589.2114.
- [24] R. Maivizhi and P. Yogesh, "Q-learning based routing for in-network aggregation in wireless sensor networks," *Wirel. Netw.*, vol. 27, no. 3, pp. 2231–2250, Apr. 2021, doi: 10.1007/s11276-021-02564-8.
- [25] S. A. Putra, B. R. Trilaksono, M. Riyansyah, and D. S. Laila, "Multiagent Architecture for Bridge Capacity Measurement System Using Wireless Sensor Network and Weight in Motion," *IEEE Trans. Instrum. Meas.*, vol. 70, pp. 1–14, 2021, doi: 10.1109/TIM.2020.3031126.
- [26] P. Di Lorenzo, S. Barbarossa, and S. Sardellitti, "Distributed Signal Processing and Optimization Based on In-Network Subspace Projections," *IEEE Trans. Signal Process.*, vol. 68, pp. 2061–2076, 2020, doi: 10.1109/TSP.2020.2981204.
- [27] S. Manikandan and M. Chinnadurai, "Effective Energy Adaptive and Consumption in Wireless Sensor Network Using Distributed Source Coding and Sampling Techniques," *Wirel. Pers. Commun.*, vol. 118, no. 2, pp. 1393–1404, May 2021, doi: 10.1007/s11277-021-08081-3.
- [28] K. S. K. M. K. N. and K. S., "A multi-Mobile Agent and optimal itinerary planning-based data aggregation in Wireless Sensor Networks," *Comput. Commun.*, vol. 184, pp. 24–35, Feb. 2022, doi: https://doi.org/10.1016/j.comcom.2021.11.019.
- [29] M. El Fissaoui, A. Beni-hssane, S. Ouhmad, and K. El Makkaoui, "A Survey on Mobile Agent Itinerary Planning for Information Fusion in Wireless Sensor Networks," *Arch. Comput. Methods Eng.*, vol. 28, no. 3, pp. 1323–1334, May 2021, doi: 10.1007/s11831-020-09417-1.

- [30] T. Alsboui, Y. Qin, R. Hill, and H. Al-Aqrabi, "An energy efficient multi-mobile agent itinerary planning approach in wireless sensor networks," *Computing*, vol. 103, no. 9, pp. 2093–2113, Sep. 2021, doi: 10.1007/s00607-021-00978-y.
- [31] T. Alsboui *et al.*, "A Dynamic Multi-Mobile Agent Itinerary Planning Approach in Wireless Sensor Networks via Intuitionistic Fuzzy Set," *Sensors*, vol. 22, no. 20, p. 8037, Oct. 2022, doi: 10.3390/s22208037.