

response to rapid changes, with predicted values remaining marginally higher than actual ones. Finally, Figure 3d illustrates predictions for 24 samples ( $n_{\text{samples}}$ ), where predicted values fall slightly below actual values, exhibiting the most significant lag while still capturing major trends in the data. Despite variations in prediction samples, all configurations effectively follow the overall pattern of soil moisture fluctuations, particularly during stable periods.

Figure 4 presents a scatter plot comparing actual values (x-axis) to predicted values (y-axis) across different prediction samples (6, 12, 18, and 24). The analysis reveals that the 12-sample model achieves the highest accuracy and consistency, with data points clustering closely around the ideal prediction line and minimal deviation. In contrast, the 6-sample model captures the overall trend but exhibits the widest spread and highest error, making it the least accurate of the four models. The 18-sample model performs well but shows minor errors at higher soil moisture levels, slightly diminishing its accuracy. The 24-sample model maintains a good fit but demonstrates increased variance at higher value ranges, indicating a slight drop in precision with longer prediction intervals. Overall, the 12-sample model stands out as the most reliable for soil moisture prediction, offering an optimal balance between accuracy and interval length.

TABLE I. ExperimentSummary

| Number of Samples ( $n_{\text{samples}}$ ) | Measurement |         |         |                |
|--------------------------------------------|-------------|---------|---------|----------------|
|                                            | RMSE        | MAE     | MAPE    | R <sup>2</sup> |
| 6                                          | 0.66378     | 0.53720 | 0.04753 | 0.79305        |
| 12                                         | 0.46281     | 0.36648 | 0.03201 | 0.89944        |
| 18                                         | 0.53350     | 0.43273 | 0.03838 | 0.86652        |
| 24                                         | 0.50695     | 0.39835 | 0.03431 | 0.87955        |

To further evaluate the effectiveness of the GRU model across different configurations, Table 1 presents a comparison of prediction results from the GRU method. The performance metrics used include Root Mean Square Error (RMSE), Mean Absolute Error (MAE), Mean Absolute Percentage Error (MAPE), and coefficient of determination ( $R^2$ ). These metrics collectively indicate that  $n_{\text{samples}} = 12$  is the most effective sample size for prediction, yielding the lowest error rates (MAPE, RMSE, MAE) and the highest  $R^2$  value. This sample likely represents an optimal balance where the GRU model can predict accurately without significant error magnitudes that can arise from either longer or shorter sample intervals.

#### IV. CONCLUSION

This study demonstrates the effectiveness of utilizing Gated Recurrent Units (GRU) to predict soil moisture levels based on environmental data collected through IoT devices. By combining soil moisture data with temperature and humidity levels, the GRU model can deliver accurate short-term predictions, crucial for enhancing irrigation efficiency. Among various prediction intervals (6, 12, 18, and 24

samples), the 12-sample model consistently achieves the highest accuracy and reliability, striking an optimal balance between precision and responsiveness. Comparative analysis through performance metrics, including RMSE, MAE, MAPE, and  $R^2$ , confirms that the 12-sample model minimizes error rates while maximizing prediction quality. These findings underscore the potential of GRU-based models for real-time soil moisture monitoring, highlighting their significance in sustainable agriculture and smart farming applications.

#### ACKNOWLEDGMENT

This work was funded by Telkom University, Indonesia under Faculty of Informatics.

#### REFERENCES

- [1] M. Furqan, S. A. Lubis, and R. L. Harahap, "Automatic Plant Watering System Based on Air Temperature and Soil Humidity Using the Fuzzy Sugeno Method," *Sinkron*, vol. 7, no. 4, pp. 2576–2583, Nov. 2022, doi: 10.33395/sinkron.v7i4.11893.
- [2] A. Kara, E. Pekel, E. Ozcetin, and G. B. Yildiz, "Genetic algorithm optimized a deep learning method with attention mechanism for soil moisture prediction," *Neural Comput Appl*, vol. 36, no. 4, pp. 1761–1772, Feb. 2024, doi: 10.1007/s00521-023-09168-7.
- [3] A. Unlukara, A. Kurunc, and B. Cemek, "Green long pepper growth under different saline and water regime conditions and usability of water consumption in plant salt tolerance," *Tarım Bilimleri Dergisi*, vol. 21, no. 2, pp. 167–176, Jan. 2015, doi: 10.1501/tarimbil\_0000001318.
- [4] "The Current Water Crisis and the Need for Alternative Farming Solutions." Accessed: Nov. 18, 2024. [Online]. Available: <https://www.edengreen.com/blog-collection/water-crisis-drought>
- [5] K. Dolaptsis *et al.*, "A Hybrid LSTM Approach for Irrigation Scheduling in Maize Crop," *Agriculture (Switzerland)*, vol. 14, no. 2, Feb. 2024, doi: 10.3390/agriculture14020210.
- [6] S. Paul and S. Singh, "Soil Moisture Prediction Using Machine Learning Techniques," in *ACM International Conference Proceeding Series*, Association for Computing Machinery, Nov. 2020, pp. 1–7. doi: 10.1145/3440840.3440854.
- [7] A. Blessy *et al.*, "Sustainable Irrigation Requirement Prediction Using Internet of Things and Transfer Learning," *Sustainability (Switzerland)*, vol. 15, no. 10, May 2023, doi: 10.3390/su15108260.
- [8] A. Dahane, R. Benameur, and B. Kechar, "An IoT Low-Cost Smart Farming for Enhancing Irrigation Efficiency of Smallholders Farmers," *Wirel Pers Commun*, vol. 127, no. 4, pp. 3173–3210, Dec. 2022, doi: 10.1007/s11277-022-09915-4.
- [9] M. T. Sattari, H. Apaydin, and S. Shamshirband, "Performance evaluation of deep learning-based gated recurrent units (GRUs) and tree-based models

for estimating ETo by using limited meteorological variables,” *Mathematics*, vol. 8, no. 6, Jun. 2020, doi: 10.3390/MATH8060972.

- [10] D. Satria and T. Hidayat, “Plant Watering System Based on the Internet of Thing,” *Jurnal Nasional Komputasi dan Teknologi Informasi*, vol. 1, no. 1, 2018.
- [11] I. Zahari, W. Mahmud, B. V. Indriyono, I. Setiarso, and I. Putra Gemilang, “Utilization Of Internet of Things for Automatic Plant Watering System Using Soil Moisture Sensor,” *JIP (Jurnal Informatika Polinema)*, vol. 9, 2023.
- [12] C. Mishra and D. L. Gupta, “Deep Machine Learning and Neural Networks: An Overview,” *IAES International Journal of Artificial Intelligence (IJ-AI)*, vol. 6, no. 2, p. 66, Jun. 2017, doi: 10.11591/ijai.v6.i2.pp66-73.
- [13] C. Mishra and D. L. Gupta, “Deep Machine Learning and Neural Networks: An Overview,” *IAES International Journal of Artificial Intelligence (IJ-AI)*, vol. 6, no. 2, p. 66, Jun. 2017, doi: 10.11591/ijai.v6.i2.pp66-73.
- [14] N. L. W. S. R. Ginantra, I. M. D. P. Asana, W. G. S. Parwita, and M. L. D. Wiadnyana, “Forecasting System Analysis using Gated Recurrent Unit Neural Network,” *Journal of System and Management Sciences*, vol. 13, no. 5, pp. 470–482, 2023, doi: 10.33168/JSMS.2023.0530.
- [15] R. Dey and F. M. Salem, “Gate-Variants of Gated Recurrent Unit (GRU) Neural Networks,” in *IEEE 60th International Midwest Symposium on Circuits and Systems (MWSCAS)*, Boston, 2017, pp. 1597–1600. doi: 10.1109/MWSCAS.2017.8053243.
- [16] J. Dawani, *Hands-On Mathematics for Deep Learning: Build a solid mathematical foundation for training efficient deep neural networks*. New York: Packt Publishing, 2020.
- [17] T. O. Hodson, “Root-mean-square error (RMSE) or mean absolute error (MAE): when to use them or not,” Jul. 19, 2022, *Copernicus GmbH*. doi: 10.5194/gmd-15-5481-2022.
- [18] A. A. Suryanto and A. Muqtadir, “Application of Mean Absolute Error (MAE) Method in Linear Regression Algorithm for Rice Production Prediction,” *SAINTEKBU: Jurnal Sains dan Teknologi*, vol. 11, no. 1, pp. 78–83, Feb. 2019.
- [19] S. Kim and H. Kim, “A new metric of absolute percentage error for intermittent demand forecasts,” *Int J Forecast*, vol. 32, no. 3, pp. 669–679, Jul. 2016, doi: 10.1016/j.ijforecast.2015.12.003.
- [20] D. Chicco, M. J. Warrens, and G. Jurman, “The coefficient of determination R-squared is more informative than SMAPE, MAE, MAPE, MSE and RMSE in regression analysis evaluation,” *PeerJ Comput Sci*, vol. 7, pp. 1–24, 2021, doi: 10.7717/PEERJ-CS.623.