

DAFTAR PUSTAKA

- Akiyama, Y., Iwaki, M., Komagamine, Y., Minakuchi, S., & Kanazawa, M. (2023). Effect of Spindle Speed and Feed Rate on Surface Roughness and Milling Duration in the Fabrication of Milled Complete Dentures: An In Vitro Study. *Applied Sciences (Switzerland)*, 13(24). <https://doi.org/10.3390/app132413338>
- Akmal Alif Bin Ismail, M., Syamil Zakaria, M., Uzair Mohd Rosli, M., & Ahmad, M. (2025). *Investigation of Machinability in Milling of PTFE under Dry and Wet Conditions* (Vol. 4, Issue 1).
- Anderson, C. G. (2022). *Polymers*. <https://doi.org/10.13140/RG.2.2.19631.61603>
- Barad, M. (2014). Design of Experiments (DOE)—A Valuable Multi-Purpose Methodology. *Applied Mathematics*, 05(14), 2120–2129. <https://doi.org/10.4236/am.2014.514206>
- Çolak, O., Kurbanoglu, C., & Kayacan, M. C. (2007). Milling surface roughness prediction using evolutionary programming methods. *Materials and Design*, 28(2), 657–666. <https://doi.org/10.1016/j.matdes.2005.07.004>
- Das, S. R., Kumar, A., & Dhupal, D. (2014). Experimental investigation on cutting force and surface roughness in machining of hardened AISI 52100 steel using cBN tool. In *Int. J. Machining and Machinability of Materials* (Vol. 18, Issue 6).
- Deng, Q., Mo, R., Chen, Z. C., & Chang, Z. (2020). An analytical approach to cutter edge temperature prediction in milling and its application to trochoidal milling. *Applied Sciences (Switzerland)*, 10(5). <https://doi.org/10.3390/app10051746>
- Dhanumalayan, E., & Joshi, G. M. (2018). Performance properties and applications of polytetrafluoroethylene (PTFE)—a review. *Advanced Composites and Hybrid Materials*, 1(2), 247–268. <https://doi.org/10.1007/s42114-018-0023-8>
- Feng, J., Wei, Z., Wang, M., Wang, X., & Guo, M. (2021). *Tool path planning for five-axis U-pass milling of an impeller*.

- Gan, Y., Wang, Y., Liu, K., Han, L., Luo, Q., & Liu, H. (2021). A novel and effective method for cryogenic milling of polytetrafluoroethylene. *International Journal of Advanced Manufacturing Technology*, 112(3–4). <https://doi.org/10.1007/s00170-020-06332-4>
- Ghosh, R., Knopf, J. A., Gibson, D. J., Mebrahtu, T., & Currie, G. (2008). Cryogenic machining of polymeric biomaterials: An intraocular lens case study. *Medical Device Materials IV: Proceedings of the Materials and Processes for Medical Devices Conference 2007*, 54–64. <https://doi.org/10.1361/cp2007mpmd054>
- Gómez, G., Fernández De Lucio, P., Del Olmo, A., Martínez De Pissón, G., Jimeno, A., González, H., & López De Lacalle, L. N. (2021). Comparison between milling roughing operations in full slotting manufacturing: trochoidal, plunge and conventional milling. *IOP Conference Series: Materials Science and Engineering*, 1193(1), 012003. <https://doi.org/10.1088/1757-899x/1193/1/012003>
- Groover, M. P. (2019). *Fundamentals of Modern Manufacturing Materials, Processes, and Systems Seventh Edition*.
- Karkalos, N. E., Karmiris-Obratański, P., Kurpiel, S., Zagórski, K., & Markopoulos, A. P. (2021). Investigation on the surface quality obtained during trochoidal milling of 6082 aluminum alloy. *Machines*, 9(4). <https://doi.org/10.3390/machines9040075>
- Ni, J., Zeng, X., Al-Furjan, M. S. H., Zhao, H., Guan, L., Cui, Z., & Han, L. (2022). Effect of Drilling Parameters on Machining Performance in Drilling Polytetrafluoroethylene. *Materials*, 15(19). <https://doi.org/10.3390/ma15196922>
- Nurhaniza, M., Ariffin, M. K. A. M., Mustapha, F., & Baharudin, B. T. H. T. (2016). Analyzing the Effect of Machining Parameters Setting to the Surface Roughness during End Milling of CFRP-Aluminium Composite Laminates. *International Journal of Manufacturing Engineering*, 2016, 1–9. <https://doi.org/10.1155/2016/4680380>
- Ramli, A. S., Sharif, S., Said, A. Y. M., & Karim, Z. (2019). Step over (Ae) effect on cutting parameters when trochoidal pocket milling of titanium

- alloy ti-6al-4v. *International Journal of Engineering and Advanced Technology*, 8(6), 3419–3423.
<https://doi.org/10.35940/ijeat.F9512.088619>
- Wagih, M., Maher, I., & Hassan, M. A. (2023). *Investigating the effects of trochoidal milling parameters on the waviness and surface roughness of P20 alloy steel slots: Analytical and Experimental*.
<https://doi.org/10.21203/rs.3.rs-3612266/v1>
- Waszczuk, K. P. (2024). Influence of Technological Parameters on the Cutting Temperature during Trochoidal Milling. *Manufacturing Technology*, 24(1), 148–153. <https://doi.org/10.21062/mft.2024.001>
- Yan, Y., Mao, Y., Li, B., & Zhou, P. (2021). Machinability of the thermoplastic polymers: Peek, pi, and pmma. *Polymers*, 13(1), 1–14.
<https://doi.org/10.3390/polym13010069>
- Zhang, X. H., Peng, F. Y., Qiu, F., Yan, R., & Li, B. (2014). Prediction of cutting force in trochoidal milling based on radial depth of cut. *Advanced Materials Research*, 852, 457–462.
<https://doi.org/10.4028/www.scientific.net/AMR.852.457>
- Zhang, Z., Cai, Y., Wang, H., Zhao, M., & Mei, J. (2024). A flexible five-axis trochoidal milling method for machining complex 3D slots. *International Journal of Advanced Manufacturing Technology*.
<https://doi.org/10.1007/s00170-024-14397-8>